



HC7(H+HC4H) HP Adapters / Plugs		
Ordering Code	HP Connection	Max. Pressure
4-450	9/16-18 UNF Plug (1/4 HP)	3.000 bar
7-432	9/16-18 UNF (1/4 HP)	3.000 bar
7-433	1/4" BSPP - 120° cone	3.000 bar
7-434	M22x1,5 Plug	3.000 bar
7-435	1/4" BSPP	800 bar
7-439	9/16-18 UNF (3/8" MP)	1.380 bar
7-441	M22x1,5 - 60° cone	3.000 bar
7-445	1/4" BSPP - 120° cone	3.000 bar
7-446	M22x1,5 - 60° cone	3.000 bar
7-447	7/16-20 UNF - 60° cone	1.035 bar
7-451-SI	1/4" BSPP + Strainer Insert	3.000 bar
7-838	1/4" NPT	1.035 bar

Material		Issue	Material Code No.
Changes Max. Pressure: 3.000 bar		Date 06-04-2017	Name L.H.
7-450 added		27-08-2021	L.H.
7-838 added & 80 Nm to 180 Nm		08-10-2021	L.H.
7-451-SI added		17-05-2022	L.H.
7-441 added		03-10-2022	L.H.
Designer	Leif Hansen	Scale 1:1	HC7(H+HC4H) Adapter Connection Possibilities
Approved by	<i>[Signature]</i>	Format A3	
Date	13-09-2009		
Tightening Torque		<small>Confidential: Property of miniBOOSTER HYDRAULICS A/S Denmark Not to be handed over to, copied or used by third party.</small> 	
M22x1,5 (Male)	9/16-18 UNF (Male)	Drawing No.: 7-900-10	
180 Nm	35 Nm		